Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the

application.

Please cancel claims 14-28 without prejudice.

Listing of Claims:

(Original) A display device comprising:

a cell having a side, the cell containing a suspension fluid and at least one

suspension particle dispersed within the suspension fluid, the suspension particle

being adapted to migrate in the suspension fluid under the influence of an electric

field; and

a light waveguide layer extending adjacent to at least the side of the cell, the

light waveguide layer adapted to conduct light into the cell through the side of the

cell.

(Original) The display device of claim 1 in which the light waveguide 2.

layer has a first surface and a first end of the cell extends beyond the first surface of

the light waveguide layer.

(Original) The display device of claim 2 in which the side tapers 3.

outwardly from the first surface toward an opposite second surface.

(Original) The display device of claim 3 in which the light waveguide 4.

layer extends around the sides of the cell.

Page 2 -

AMENDMENT

Serial No. 10/757,915

HP Docket No. 200210082-1

KH Docket No. HPCC 399

PAGE 5/14 * RCVD AT 4/15/2005 7:53:02 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-1/2 * DNIS:8729306 * CSID:5039729115 * DURATION (mm-ss):08-10

5. (Original) The display device of claim 4 in which a second end of the

cell extends beyond the second surface of the layer.

6. (Original) An electrophoretic display device comprising:

a plurality of capsules, each capsule having a narrow end and a broad end,

and sides connecting the ends, each capsule containing a suspension fluid and a

plurality of suspension particles dispersed within the suspension fluid, the

suspension particles being adapted to migrate in the suspension fluid under the

influence of an electric field;

a light waveguide layer surrounding the sides of the capsules and adapted to

conduct light along the light waveguide layer and laterally into the capsules through

the sides, the narrow ends of the capsules extending through the light waveguide

layer; and

electrodes supported adjacent to opposite ends of the capsules.

7. (Original) A method of making a display element comprising:

forming a light waveguide layer adapted to transmit light along a light path

defined by the light waveguide layer; and

forming a cell containing a suspension fluid and at least one suspension

particle dispersed within the suspension fluid, the suspension particle being adapted

to migrate in the suspension fluid under the influence of an electric field, the cell

extending into the light waveguide layer.

8. (Original) The method of claim 7 further comprising directing light

along the light waveguide layer and laterally into the cell through the side of the

capsule.

Page 3 -

AMENDMENT

Serial No. 10/757,915

HP Docket No. 200210082-1

KH Docket No. HPCC 399

04/15/05 15:59 \$5039729115 KOLISCH HARTWELL \$\overline{Q}\)007/014

9. (Original) The method of claim 7 in which forming a cell includes

forming a membrane enclosing the suspension fluid and at least one particle, the

method further comprising forming a passageway extending through the light

waveguide layer, and positioning the cell in the passageway with a portion of the cell

extending beyond the light waveguide layer.

10. (Original) The method of claim 9 in which forming a passageway

includes forming a passageway tapering between a first opening and a second

opening smaller than the first opening, and positioning the cell includes inserting the

cell into the first opening.

11. (Original) The method of claim 9 in which positioning the cell includes

at least one of pressing the cell into the passageway, and pulling the cell into the

passageway.

12. (Original) The method of claim 11 in which forming a passageway

includes forming a passageway between first and second openings, positioning the

cell includes positioning the cell against the first opening, and pulling the cell

includes applying a reduced ambient pressure to the second opening sufficient to

draw the capsule into the passageway.

13. (Original) The method of claim 12 in which the passageway extends

through the light waveguide layer, and applying a reduced ambient pressure includes

applying a reduced ambient pressure sufficient to draw the portion of the cell through

the passageway until the portion extends beyond the light waveguide layer.

Page 4 -

AMENDMENT

Serial No. 10/757,915

HP Docket No. 200210082-1

KH Docket No. HPCC 399

- 14. (Cancelled)
- (Cancelled) 15.
- 16. (Cancelled)
- 17. (Cancelled)
- 18. (Cancelled)
- 19. (Cancelled)
- 20. (Cancelled)
- 21. (Cancelled)
- 22. (Cancelled)
- 23. (Cancelled)
- 24. (Cancelled)
- 25. (Cancelled)
- 26. (Cancelled)
- 27. (Cancelled)
- 28. (Cancelled)
- (Original) A display device comprising: 29.

cell means containing a suspension fluid and at least one suspension particle dispersed within the suspension fluid, the suspension particle being adapted to migrate in the suspension fluid under influence of an electric field; and light waveguide means extending adjacent a side of the cell means, the light waveguide means being adapted to conduct light into the cell means through the side of the cell means.

KOLISCH HARTWELL

AMENDMENT Page 5 -Serial No. 10/757,915 HP Docket No. 200210082-1 KH Docket No. HPCC 399